



Product Service

CERTIFICATE

No. Z1A 16 06 14229 050

Holder of Certificate: Reutlinger GmbH



Offenbacher Landstr. 190
60599 Frankfurt
GERMANY

Certification Mark:



Product: Cable holders

Tested according to: PPP 52347B:2016
AfPS GS 2014:01 PAK 3.1

The product meets the safety and health requirements of the German Product Safety Act section 20 to 22 ProdSG. The certification marks shown above can be affixed on the product. It is not permitted to alter the certification marks in any way. In addition the certificate holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. See also notes overleaf.

Test report no.: 713082469

Valid until: 2021-06-16

Handwritten signature of Horst Kristen

Date, 2016-06-20 (Horst Kristen)





CERTIFICATE
No. Z1A 16 06 14229 050

Model(s): **50 SV III**
 66 SV III
 80 SV III

Parameters:	type:	50 SV III	66 SV III	80 SV III
	cable-Ø:	4,0 mm	6,0 mm	6,0 mm
	working load:	120 kg	270 kg	270 kg
	cable-Ø:	5,0 mm	6,35 mm	8,0mm
	workin load:	180 kg	300 kg	480 kg
	allowed cable:			
	cable type:	galvanized steel, 6x7 + 1 FE according to DIN EN 12385-4:2008		
	cable strength:	minimum 1770 N/mm ²		
	cable type:	galvanized steel, 6x19 + 1 FE according to DIN EN 12385-4:2008		
	cable strength:	minimum 1770 N/mm ²		
	cable type:	galvanized steel, 6x19 + 1 SE according to DIN EN 12385-4:2008		
	cable strength:	minimum 1770 N/mm ²		
	cable type:	galvanized steel, 6x37 + 1 SE according to DIN EN 12385-4:2008		
	cable strength:	minimum 1770 N/mm ²		
	cable type:	galvanized steel, 6x19 + 1 SE according to DIN EN 12385-4:2008		
	cable strength:	minimum 1960 N/mm ²		
	cable type:	stainless steel, 6x19 + 1 SE according to DIN EN 12385-4:2008		
	cable strength:	minimum 1570 N/mm ²		
	remark:	Only for static loads. Cable glider are inappropriate for all kind of dynamic, movable suspensions.		

Factory(ies): 14229