



<p style="text-align: center;">TÜV / GS Workingload Rigging-cable holder (Safety factor 5)</p> 	permitted cable construction / nominal tensile strength				
	6x7+1FE 1770 N/mm ²	6x7+1FE 1770 N/mm ²	6x19+FE 1770 N/mm ²	6x19+FE 1770 N/mm ²	6x19+FE 1770 N/mm ²
	6x19+FE 1770 N/mm ²	6x19+FE 1770 N/mm ²	6x19+SE 1960 N/mm ²	6x19+SE 1770 N/mm ²	6x19+SE 1960 N/mm ²
					6x37+FE 1770 N/mm ²
	Cable-ø in mm / Working load in kg				
Cable Holder type	4,0 mm	5,0 mm	6,0 mm	6,35 mm	8,0 mm
50 SV III	120	180	-	-	-
66 SV III	-	-	270	300	-
80 SV III	-	-	270	-	480

<p style="text-align: center;">DGUV instruction Workingload Rigging-cable holder (Safety factor 10)</p> 	permitted cable construction / nominal tensile strength				
	6x7+1FE 1770 N/mm ²	6x7+1FE 1770 N/mm ²	6x19+FE 1770 N/mm ²	6x19+FE 1770 N/mm ²	6x19+FE 1770 N/mm ²
	6x19+FE 1770 N/mm ²	6x19+FE 1770 N/mm ²	6x19+SE 1960 N/mm ²	6x19+SE 1770 N/mm ²	6x19+SE 1960 N/mm ²
					6x37+FE 1770 N/mm ²
	Cable-ø in mm / Working load in kg				
Cable Holder type	4,0 mm	5,0 mm	6,0 mm	6,35 mm	8,0 mm
50 SV III	60	90	-	-	-
66 SV III	-	-	135	150	-
80 SV III	-	-	135	-	240